


ecora

Permeable ground
stabilization system

ECORASTER® TE40 XXL



recommended for

paddocks, riding areas & halls

open & active stables

paths, feeding areas, access roads & parking spaces

20 years
WARRANTY

Dimensions	133 x 100 x 4 cm
Wall thickness	up to 3.0 mm
Weight/m ²	4.8 kg
Weight/piece	6.35 kg
Dimensional stability	-50° / +90° C

Moisture absorption	0.01 %
Interlock	21 notched connectors/pallet
Solubility	resistant to acids, alkalis, alcohol, oil and petrol (de-icing salt, ammonia, acid rain, etc.)
Max. open surface	approx. 87 %
Material	LD-PE, recycled
Loadability	up to 800 t/m ² (depending on fill type)
Compressive strength	up to 20 t point axle load (DIN 1072)
UV-resistant and weatherproof	according to DIN EN ISO 4892-2 & DIN EN 60068-2-5
Environmental compatibility	environmentally neutral according to OECD 202:2004
Highly durable	according to DIN EN 124:2011 (D400)
Tensile strength	> 5 kN/m

Package

Standard installation unit	1 layer (equals 1.33 m ²)
Layers/pallet	56
Area/pallet	74.67 m ²
Dimensions	105 x 135 x 246 cm
Weight/pallet	approx. 365 kg (incl. plastic pallet and packaging)

NOTE:

- Please note the installation instructions on our website! Subject to change without prior notice. E. & O. E.
- The listed details are nominal dimensions and subject to a certain tolerance due to material changes.

ecora.de